

In the Claims:

1. (Currently Amended): A module for screening or diverting particulate material comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module or a diverting member for redirecting the flow path of the said particulate material, the screening or diverting member including a frame engagement member for interlockingly mounting the screening or diverting member onto a reinforcing support frame such that the screening or diverting member is readily attachable to and detachable therefrom, and such that particulate material passing through the screening member passes through the reinforcing support frame, the frame engagement member comprising a detent extending from a lower surface of the screening or diverting member for readily and interlockingly mounting the screening or diverting member onto said frame, the screening or diverting member being further interlockingly mountable onto a plurality of posts such that the screening or diverting member is readily detachable therefrom.

2. (Original): A module according to claim 1, wherein said screening or diverting member and said frame are configured to mate with a portion of each of said posts by snap-fit engagement.

3. (Original): A module according to claim 1, wherein said screening or diverting member comprises a substantially rectangular shape having a plurality of corners, and wherein post engagement members are located at each of the corners of the screening or diverting member for interlockingly mounting said screening or diverting member to each of said posts.

4. (Cancelled)

5. (Original): A module according to claim 1, wherein at least a portion of a surface of said frame engagement member includes a gripping surface for engaging a complementary gripping surface on an engagement surface of said frame, thereby providing increased frictional mating engagement between said screening or diverting member and said frame.

6. (Original): A module according to claim 1, wherein each of said posts is joined to a mounting piece.

7. (Original): A module according to claim 6, wherein said mounting piece comprises a structural bar, a rod, or a tube.

8. (Original): A module according to claim 1, wherein each said post is mounted to an underlying support member of a deck assembly.

9. (Original): A module according to claim 1, which is formed of at least one polymeric material.

10. (Original): A module according to claim 1, wherein at least one frame is formed of a metal material or a polymeric material.

11. (Original): A module according to claim 1, wherein each of the posts includes at least one of a slot into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and wherein each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

12. (Original): A module according to claim 11, wherein said frame slot is arcuate-shaped.

13. (Original): A module according to claim 1, wherein each of said posts comprises at least one of a slot or a recess for interlockingly engaging with said module, and at least one frame slot is disposed within said posts.

14. (Original): A module according to claim 1, wherein at least one said frame has a substantially rectangular-shaped perimeter including at least one arcuate-shaped corner.

15. (Original): A module according to claim 1, wherein at least one said frame includes at least one laterally extending bracing member for maintaining the structural integrity of said frame.

16. (Original): A module according to claim 1, wherein said screening or diverting member defines a plurality of receptacles, each receptacle receiving and retaining a portion of each of said posts.

17. (Original): A module according to claim 1, which comprises a frame engagement member extending from a lower surface thereof for readily and interlockably mounting said module onto at least one said frame.

18. (Cancelled)

19. (Cancelled)

20. (Original): A module according to claim 1, wherein each of the posts includes at least one recess into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and wherein each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

21. (Currently Amended) A method for producing a module for screening or diverting particulate material, comprising:

forming a module comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module and a diverting member for redirecting the flow path of the said particulate material; and

configuring said screening or diverting module for interlockingly and detachably mountability onto a reinforcing support frame and onto a plurality of posts which removably and interlockingly support a reinforcing support frame, said module being disposable over at least a portion of at least one of the posts, said screening or diverting module including a frame engagement member comprising a detent

extending from a lower surface of the screening or diverting member for readily and interlockingly mounting the screening or diverting member onto said frame,

the module being positionable on the reinforcing support frame so that particulate material passing through the screening module passes through the reinforcing support frame.

22. (Original): A method according to claim 21, wherein said screening or diverting member and said frame are configured to mate with a portion of each of said posts by snap-fit engagement.

23. (Original): A method according to claim 21, wherein said screening or diverting member comprises a substantially rectangular shape having a plurality of corners, and wherein post engagement members are located at each of the corners of the screening or diverting member for interlockingly mounting said screening or diverting member to each of said posts.

24. (Cancelled)

25. (Original): A method according to claim 21, wherein at least a portion of a surface of said frame engagement member includes a gripping surface for engaging a complementary gripping surface on an engagement surface of said frame, thereby providing increased frictional mating engagement between said screening or diverting member and said frame.

26. (Original): A method according to claim 21, wherein each of said posts is joined to a mounting piece.

27. (Original): A method according to claim 26, wherein each said mounting piece comprises a structural bar, a rod, or a tube.

28. (Original): A method according to claim 21, wherein each said post is mounted to an underlying support member of a deck assembly.

29. (Currently amended): A method according to claim 21, ~~which~~ wherein said module is formed of at least one polymeric material.

30. (Original): A method according to claim 21, wherein at least one frame is formed at least one of a metal and a polymeric material.

31. (Original): A method according to claim 21, wherein each of the posts includes at least one of a slot into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and wherein each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

32. (Original): A method according to claim 21, wherein said frame slot is arcuate-shaped.

33. (Original): A method according to claim 21, wherein each of said posts comprises at least one of a slot or a recess for interlockingly engaging with said module, and at least one frame slot is disposed within said posts.

34. (Original): A method according to claim 21, wherein at least one said frame has a substantially rectangular-shaped perimeter including at least one arcuate-shaped corner.

35. (Original): A method according to claim 21, wherein at least one said frame includes at least one laterally extending bracing member for maintaining the structural integrity of said frame.

36. (Cancelled)

37. (Original): A method according to claim 21, which comprises a frame engagement member extending from a lower surface thereof for readily and interlockably mounting said method onto at least one said frame.

38. (Cancelled)

39. (Cancelled)

40. (Original): A method according to claim 1, wherein each of the posts includes at least one of a recess into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and wherein each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

Add the following new claims 41-50.

41. (New) A module for screening or diverting particulate material comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module or a diverting member for redirecting the flow path of the said particulate material, the screening or diverting member including a frame engagement member for interlockingly mounting the screening or diverting member onto a reinforcing support frame such that the screening or diverting member is readily attachable to and detachable therefrom, and such that particulate material passing through the screening member passes through the reinforcing support frame, the screening or diverting member being further interlockingly mountable onto a plurality of posts such that the screening or diverting member is readily detachable therefrom, wherein each of the posts includes at least one of a slot into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and wherein each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

42. (New) A module for screening or diverting particulate material comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module or a diverting member for redirecting the flow path of the said particulate material, the screening or diverting member including a frame engagement member for interlockingly mounting the screening or diverting member onto a reinforcing support frame such that the screening or diverting member is readily attachable to and detachable therefrom, and such that particulate material passing through the screening member passes through the

reinforcing support frame, the screening or diverting member being further interlockingly mountable onto a plurality of posts such that the screening or diverting member is readily detachable therefrom, wherein said frame slot is arcuate-shaped.

43. (New) A module for screening or diverting particulate material comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module or a diverting member for redirecting the flow path of the said particulate material, the screening or diverting member including a frame engagement member for interlockingly mounting the screening or diverting member onto a reinforcing support frame such that the screening or diverting member is readily attachable to and detachable therefrom, and such that particulate material passing through the screening member passes through the reinforcing support frame, the screening or diverting member being further interlockingly mountable onto a plurality of posts such that the screening or diverting member is readily detachable therefrom, wherein at least one said frame having a substantially rectangular-shaped perimeter including at least one arcuate-shaped corner.

44. (New) A module for screening or diverting particulate material comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module or a diverting member for redirecting the flow path of the said particulate material, the screening or diverting member including a frame engagement member for interlockingly mounting the screening or diverting member onto a reinforcing support frame such that the screening or diverting member is readily attachable to and detachable therefrom, and such that particulate material passing through the screening member passes through the reinforcing support frame, said frame engagement member extending from a lower surface thereof for readily and interlockably mounting said module onto at least one said frame.

45. (New) A module for screening or diverting particulate material comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the

predetermined size to pass through the module or a diverting member for redirecting the flow path of the said particulate material, the screening or diverting member including a frame engagement member for interlockingly mounting the screening or diverting member onto a reinforcing support frame such that the screening or diverting member is readily attachable to and detachable therefrom, and such that particulate material passing through the screening member passes through the reinforcing support frame, the screening or diverting member being further interlockingly mountable onto a plurality of posts such that the screening or diverting member is readily detachable therefrom, wherein each of the posts includes at least one recess into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and wherein each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

46. (New) A method for producing a module for screening or diverting particulate material, comprising:

forming a module comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module and a diverting member for redirecting the flow path of the said particulate material; and

configuring said screening or diverting module for interlockingly and detachably mountability onto a reinforcing support frame and onto a plurality of posts which removably and interlockingly support a reinforcing support frame, said module being disposable over at least a portion of at least one of the posts,

the module being positionable on the reinforcing support frame so that particulate material passing through the screening module passes through the reinforcing support frame, and said screening or diverting member comprising a substantially rectangular shape having a plurality of corners, and said post engagement members being located at each of the corners of the screening or diverting member for interlockingly mounting said screening or diverting member to each of said posts.

47. (New) A method for producing a module for screening or diverting particulate material, comprising:



forming a module comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module and a diverting member for redirecting the flow path of the said particulate material; and configuring said screening or diverting module for interlockingly and detachably mountability onto a reinforcing support frame and onto a plurality of posts which removably and interlockingly support a reinforcing support frame, said module being disposable over at least a portion of at least one of the posts,

the module being positionable on the reinforcing support frame so that particulate material passing through the screening module passes through the reinforcing support frame, each of the posts including at least one of a slot into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and each of the posts further comprising at least one frame slot within which a corner of each said frame is readily and interlocking mounted.

48. (New) A method for producing a module for screening or diverting particulate material, comprising:

forming a module comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module and a diverting member for redirecting the flow path of the said particulate material; and configuring said screening or diverting module for interlockingly and detachably mountability onto a reinforcing support frame and onto a plurality of posts which removably and interlockingly support a reinforcing support frame, said module being disposable over at least a portion of at least one of the posts,

the module being positionable on the reinforcing support frame so that particulate material passing through the screening module passes through the reinforcing support frame, wherein at least one said frame having a substantially rectangular-shaped perimeter including at least one arcuate-shaped corner.

49. (New) A method for producing a module for screening or diverting particulate material, comprising:

forming a module comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing

particulate material up to the predetermined size to pass through the module and a diverting member for redirecting the flow path of the said particulate material; and configuring said screening or diverting module for interlockingly and detachably mountability onto a reinforcing support frame and onto a plurality of posts which removably and interlockingly support a reinforcing support frame, said module being disposable over at least a portion of at least one of the posts, the module being positionable on the reinforcing support frame so that particulate material passing through the screening module passes through the reinforcing support frame, a frame engagement member extending from a lower surface thereof for readily and interlockably mounting said method onto at least one said frame.

50. (New) A method for producing a module for screening or diverting particulate material, comprising:

forming a module comprising either one of a screening member having an array of sieve apertures of a predetermined size defined therein for allowing particulate material up to the predetermined size to pass through the module and a diverting member for redirecting the flow path of the said particulate material; and configuring said screening or diverting module for interlockingly and detachably mountability onto a reinforcing support frame and onto a plurality of posts which removably and interlockingly support a reinforcing support frame, said module being disposable over at least a portion of at least one of the posts,

the module being positionable on the reinforcing support frame so that particulate material passing through the screening module passes through the reinforcing support frame, each of the posts including at least one recess into which at least one post engagement member located on a corner of each said module is interlockingly engaged, and each of the posts further comprises at least one frame slot within which a corner of each said frame is readily and interlocking mounted.